



# HSM SECURIO B32 - 1/32" x 7/16"


## **HSM SECURIO B32 document shredder**

High quality materials, proven quality – the reliable security partner in the workplace. With an intake width of 310 mm, the document shredder effortlessly shreds DIN A3 paper. It is the perfect device for working groups.

# **Technical data**

Order number:	1825113	Intake width:	12.2"
EAN	4026631043151	Container volume /	21.7 gal
Cutting type:	particle cut	collecting:	
Cutting size:	1/32" x 7/16"	Collection volume in sheets (80 g):	818
Security level (DIN 66399):	F-3 P-6	Noise level (idle operation):	ca. 56 dB(A)
Cutting capacity in sheets 80g/m²:	6	Width x Depth x Height:	19.57" x 15.67" x 31.22"
-		Weight:	59.52 lb
Power consumption:	500 W	Characteristic to	Decree Charles and Lance
Voltage / Frequency:	120 V / 60 Hz	Shredder material:	Paper, Staples and paper clips

## **Product information**



The induction-hardened, solid steel cutting rollers guarantee durability.



The full bin is indicated via the display and the machine switches off automatically.



The device can be intuitively operated with the multifunction element.





#### For continuous operation

The powerful motor ensures a high cutting capacity and reliable continuous operation.



#### **Energy-saving**

In stand-by mode, intelligent control programme EcoSmart ensures there is an exceptionally low power consumption of 0.1 watts.



## High level of user safety

The safety element prevents unintentional entry of materials into the machine and thereby increases the user safety.



# **Automatic start/stop**

The operation is very easy: the device starts automatically when fed paper and automatically stops after shredding is complete.



# Display bin full

The full bin is indicated via the display and the machine switches off automatically.



# **Filling level indication**

The filling level of the waste container can be seen at all times through the inspection window.













Lifetime warranty on solid steel cutting rollers at security levels P-2 to P-5 (according to ISO/IEC 21964).



